



ジェイダブルシステム
JW-system co.,ltd.

Light efficiency:

83 Lumen/Watt

Light quality:

CRI: 90.7

Color temperature:

2624 K


Output: 793 lm

Peak: 212 cd

Power: 9.5 W

24.0V @ 0.396A

2 PLANES



Product name:

LED lightbar F308 2700K


Diffuser LF1EB308VDB093

Date and time:

2024/09/14 22:17:10

Item number:

LF1EB308VDB093



Beam angle

124.6°

Color






CIE1931

x: 0.470


y: 0.419

Spectra






TM30: 90.8



CRI: 90.7 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
90.49	95.70	98.41	91.65	90.80	97.03	88.50	73.09	41.28	90.40	94.60	83.56	91.95	99.73	82.72


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
87.12	90.08	90.82	93.98	95.63	95.84	94.64	96.14	92.98	90.73	90.41	90.08	88.64	85.03	89.52	83.08

CQS Q values


Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
83.51	93.16	91.51	90.58	91.52	91.91	91.95	93.04	93.03	91.26	91.07	91.38	90.44	80.77	82.06

CQS: 88.8



Color parameters

CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Duv
2624 K	90.7	41.3	90.8	96.4	88.8	0.5	0.4	0.3	0.4	0.0022



Intensities in 0° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
212	210	205	194	180	163	142	119	96	74	55	41	31	24	19	16	14	10	7	4
100%	99%	97%	92%	85%	77%	67%	56%	46%	35%	26%	19%	14%	11%	9%	8%	6%	5%	3%	2%

Intensities in 90° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
212	209	201	187	167	143	114	82	48	16	2	2	2	2	2	2	3	3	3	3
100%	99%	95%	88%	79%	68%	54%	39%	22%	8%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%

Intensities in 180° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
212	210	205	194	180	163	142	119	96	74	55	41	31	24	19	16	14	10	7	4
100%	99%	97%	92%	85%	77%	67%	56%	46%	35%	26%	19%	14%	11%	9%	8%	6%	5%	3%	2%

Intensities in 270° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
212	209	201	187	167	143	114	82	48	16	2	2	2	2	2	2	3	3	3	3
100%	99%	95%	88%	79%	68%	54%	39%	22%	8%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%

Beam angle 50%	Field angle 10%	Cutoff angle 2.5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
124.6°	200.8°	252.0°	64.0%	42.4%