


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:24.246V I:1.2849A P:31.153W PF:1.0000 Freq:0Hz UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:3325.22x1 lm		
NAME: PLHE28G300V4 (Green)	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: EVERFINE	SUR.: 240*480MM	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 106.74 lm/W			
MODEL	IP54 纳米	I _{max} (cd)	976.7	S/MH(C0/180)	1.34
NOMINAL POWER(W)	30	LOR(%)	100.0	S/MH(C90/270)	1.37
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	3325.2	η UP,DN(C0-180)	0.6,49.5
NOMINAL FLUX(lm)	3325.22	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.6,49.3
LAMPS INSIDE	1	η up(%)	1.2	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	24	η down(%)	98.8	CIBSE SHR MAX	1.55

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)




C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3℃
 Operators:DAMIN
 Test Date:2025-12-04

γ Range: 0 - 180DEG
 γ Interval: 0.5DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.471
 Humidity:65.0%
 Test Distance:6.490m [K=1.0000]
 Remarks:

AAI Figure

Test:U:24.246V I:1.2849A P:31.153W PF:1.0000 Freq:0Hz		
UTHDi:0.00% ITHDi:0.00% KDisp:0 Lamp Flux:3325.22x1 lm		
NAME: PLHE28G300V4 (Green)	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: EVERFINE	SUR.: 240*480MM	Shielding Angle:



Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3℃
Operators:DAMIN
Test Date:2025-12-04

γ Range: 0 - 180DEG
γ Interval: 0.5DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.00.471
Humidity:65.0%
Test Distance:6.490m [K=1.0000]
Remarks: